PART NUMBER REV. DATE COMMENTS INITIAL TMPD4-00450600-15N 2020/4/25 **ENGINEERING RELEASE** В 95 **Specifications RoHS Compliant** 88 11 Frequency Range 0.45-6GHz **Insertion Loss** 2.3dB max **Nominal Splitter Loss** 6.02dB typ VSWR(input) 1.6:1 max VSWR(output) 1.6:1 max 18dB min Isolation Amplitude Balance ± 0.3dB max Phase Balance ±5° max Impedance 50 Ohm Power Handling 15W Type N-Female Connectors **Connector Body** Stainless Steel, Passivated 4-Φ 3.5 Center Contact Gold Plated Beryllium Copper THRU **Dimensions** 135 × 95 × 21mm Surface Finish Nickel Plated Output3 Output2 Material Aluminum Temperature Range -40°C~+70°C 25

Drawing not to scale, units:mm



www.titan-microwave.com Tel: +86 130 866 58398

Email: sales@titan-microwave.com chris@titan-microwave.com

PART NUMBER TMPD4-00450600-15N		DESCRIPTION Power Divider, 4 Way, 0.45-6GHz 15W, Type N-Female
CAGE CODE	SIGNATURE	
EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR THIS DRAWING OR SPECIFICATION IS PROPERTY OF TITAN MICROWAVE INC. IT IS ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS.		

75