PART NUMBER

TMPD2-06001800-100SA

| REV. | DATE | COMMENTS | INITIAL |
|------|-----------|---------------------|---------|
| Α | 2020/4/25 | ENGINEERING RELEASE | |

RoHS Compliant

Specifications


Power Handling


Frequency Range 6-18GHz
Insertion Loss 0.5dB max
Nominal Splitter Loss 3.0dB typ
VSWR(input) 1.35:1 max
Amplitude Balance ± 0.25dB max
Phase Balance ± 4° max
Impedance 50 Ohm

Connectors SMA-Male & SMA-Female
Connector Body Stainless Steel, Passivated
Center Contact Gold Plated Beryllium Copper

100W

Dimensions $47 \times 36 \times 13$ mm Surface Finish Nickel Plated Material Aluminum 6061 Temperature Range $-40^{\circ}\text{C} \sim +70^{\circ}\text{C}$





Drawing not to scale, units:mm



www.titan-microwave.com Tel: +86 130 866 58398

Email: sales@titan-microwave.com chris@titan-microwave.com

| PART NUMBER | | DESCRIPTION | |
|-----------------------|--------------------------|--|--|
| TMPD2-060 | 01800-100SA | Power Divider, 2 Way, 6-18GHz 100W, SMA-Female/Male | |
| CAGE CODE | SIGNATURE | | |
| | | | |
| | | | |
| EXCEPT AS OTHERWISE F | PROVIDED BY CONTRACTOR | | |
| THIS DRAWING OR SPEC | IFICATION IS PROPERTY OF | | |
| TITAN MICROWAVE INC. | IT IS ISSUED IN STRICT | | |
| CONFIDENCE AND SHAL | L NOT BE REPRODUCED OR | | |
| USED AS THE BASIS. | | | |
| | | | |