


REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/2/22	C. Chen

TECHNICAL DATA

► Electrical Data(50Ω, 25°C)

Frequency Range	4~8GHz
Output Power(CW, Psat)	≥47dBm
Gain	≥47dB
Gain Flatness	≤3±1dB
Input VSWR	≤1.7:1
Input Power	2±1dBm
Harmonic@Worst point	≤-20dBc
Spurious	≤-65dBc
Temperature Protection	Over 80°C protection
PTT Port	Default OFF, 3.3-5V ON
Operating Voltage	+28V~+30V
Operating Current	≤7-9A
VCC/Current Reference	28V/12A



► Mechanical Data

Dimensions	198×101.7×27.5mm
Input Connector	SMA-Female
Output Connector	SMA-Female
28V Power Supply Connector	Feedthru Capacitor
Weight	1Kg max
Package	1 piece/box

► Environmental Data

Operating Temperature	-25°C~+55°C
-----------------------	-------------

! Stress above these ratings may cause permanent damage to the device

Radiator/Heatsink required during operation or test

Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 22/02/23	TITLE: Power Amplifier, 4-8GHz, Gain 47dB, Output Power 47dBm, +28V, SMA- Female	PART No.: TMPA-04000800-4747	DIMENSIONS IN MILLIMETERS(mm)
ENGINEER: J. Zhu 22/02/23			
APPROVED: C. Chen 22/02/23			
TOLERANCE UNLESS OTHERWISE SPECIFIED			
x ±0.50 [0.019"]			
.x ±0.20 [0.008"]			
.xx ±0.10 [0.004"]			
ANGLES ±1°			
SIZE: A4	SCALE:	SHEET: 1/1	REV: A

 成都巨人微波
TITAN MICROWAVE INC.
- A Professional RF & Microwave Components Supplier -

www.titan-microwave.com