REV DESCRIPTION OF REVISION		Ву	DATE	APPROVED
Α	INITIAL RELEASE	C. Cai	2023/9/12	C. Chen

TECHNICAL DATA

► Electrical Data

Pass Band Frequency DC-18GHz
Pass Band Insertion Loss ≤2.0dB
Pass Band VSWR ≤1.5:1

Stop Band Rejection 60dB typical@20-30GHz

Impedance 50 Ohms Power Handling ≤15W


► Mechanical Data

Dimensions 35×17×10mm

Connectors SMA-Female(stainless steel)
Material 6061 Aluminum Alloy

► Environmental Data

Temperature Range -40°C ~+85°C (design assurance)



Notes:

- 1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- 2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 12/09/23						
ENGINEER: J. Zhu 12/09/23						
APPROVED: C. Chen 12/09/23						
TOLERANCE UNLESS OTHERWISE SPECIFIED						
x	±0.50	[0.019"]				
.x	±0.20	[0.008"]				
.xx	±0.10	[0.004"]				
ANGLES	±1°					

TITLE:

Low Pass Filter, DC-18GHz, Stop Band Rejection 60dB, 15W, SMA-Female

PART No.:

TLF-18000-60S



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4 SCALE:

SHEET: 1/1 REV: