

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/12/21	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	12-18GHz
Insertion Loss	2.8dB max
(excluding theoretical loss 10.8dB)	
Input Port VSWR	1.35 typ, 1.6 max
Output Port VSWR	1.22 typ, 1.5 max
Isolation	16dB min
Amplitude Balance	±1.0dB
Phase Balance	±10°
Impedance	50 Ohms
Power Rating	10W(as a splitter)
Power Rating	1W(as a combiner)

► Mechanical Data

Input/Output Connectors	SMA-Female
Dimensions	166×102×10mm
Surface Finish	Black/Gray Painted

► Environmental Data

Operating Temperature	-45°C~+85°C
-----------------------	-------------



Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 21/12/22	TITLE: Power Divider, 12 Way, 12~18GHz, 10W, SMA-Female	PART No.: TMPD12-12001800-10S	DIMENSIONS IN MILLIMETERS(mm) SIZE: A4 SCALE: SHEET: 1/1 REV: A
ENGINEER: J. Zhu 21/12/22			
APPROVED: C. Chen 21/12/22			
TOLERANCE UNLESS OTHERWISE SPECIFIED			
x ±0.50 [0.019"]			
.x ±0.20 [0.008"]			
.xx ±0.10 [0.004"]			
ANGLES ±1°			

 成都巨人微波
TITAN MICROWAVE INC.
- A Professional RF & Microwave Components Supplier -

www.titan-microwave.com