

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/6/15	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	3000~3500MHz
Insertion Loss	1.0dB max
(excluding theoretical insertion loss 10.8dB)	
Isolation	20dB min
Input VSWR	1.30 max
Output VSWR	1.20 max
Amplitude Balance	±0.4dB
Phase Balance	±4°
Power Rating	10W(as a splitter)
Power Rating	1W(as a combiner)
Impedance	50 Ohms

► Mechanical Data

Dimensions	165×86×12mm
Input/Output Connectors	SMA-Female
Surface Finish	Sandblasting Natural Color Conductive Oxidation
Weight	450g

► Environmental Data

Operating Temperature	-35°C~+75°C
-----------------------	-------------



Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 15/06/22	TITLE: Power Divider, 12-Way, 3-3.5GHz, 10W, SMA- Female	PART No.: TMPD12-03000350-10S	 TITAN MICROWAVE INC. <i>A Professional RF & Microwave Components Supplier</i> www.titan-microwave.com
ENGINEER: J. Zhu 15/06/22			
APPROVED: C. Chen 15/06/22			
TOLERANCE UNLESS OTHERWISE SPECIFIED			
x ±0.50 [0.019"]			
.x ±0.20 [0.008"]			
.xx ±0.10 [0.004"]			
ANGLES ±1°			
			DIMENSIONS IN MILLIMETERS(mm)
SIZE: A4	SCALE:	SHEET: 1/1	REV: A