

TECHNICAL DATA

► Electrical Data


Frequency Range	400~6000MHz
Insertion Loss	5.8dB max (excluding theoretical insertion loss 10.8dB)
Isolation	18dB min
Input VSWR	1.6:1 max
Output VSWR	1.3:1 max
Amplitude Balance	±1.0dB
Phase Balance	±10°
Power Rating	10W(as a splitter)
Power Rating	1W(as a combiner)
Impedance	50 Ohms

► Mechanical Data

Dimensions	240×178×12mm
Input/Output Connectors	SMA-Female
Surface Finish	Sandblasting Natural Color Conductive Oxidation

► Environmental Data

Operating Temperature	-35°C~+75°C
-----------------------	-------------



DRAWN: L. Ma 15/06/22
ENGINEER: J. Zhu 15/06/22
APPROVED: C. Chen 15/06/22
TOLERANCE UNLESS OTHERWISE SPECIFIED
$x \pm 0.50$ [0.019"] $.x \pm 0.20$ [0.008"] $.xx \pm 0.10$ [0.004"] ANGLES $\pm 1^\circ$

TITLE:
Power Divider, 12-Way,
0.4-6GHz, 10W, SMA-Female

PART No.: TMPD12-00400600-10S

TITAN MICROWAVE INC.
A Professional RF & Microwave Components Supplier

www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
----------	--------	------------	--------

Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY