

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/12/21	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	2.35~2.55GHz
Insertion Loss	0.5dB max
(excluding theoretical loss 9.0dB)	
Input Port VSWR	1.18 typ, 1.45 max
Output Port VSWR	1.15 typ, 1.25 max
Isolation	18dB min, 26dB typ
Amplitude Balance	±0.2dB
Phase Balance	±5°
Impedance	50 Ohms
Power Rating	300W(as a splitter)
Power Rating	20W(as a combiner)

► Mechanical Data

Input Connector	N-Female
Output Connectors	SMA-Female
Dimensions	204×158×24mm
Surface Finish	Sandblasting natural color conductive oxidation

► Environmental Data

Operating Temperature	-35°C~+75°C
-----------------------	-------------



Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 21/12/22
ENGINEER: J. Zhu 21/12/22
APPROVED: C. Chen 21/12/22
TOLERANCE UNLESS OTHERWISE SPECIFIED

x ±0.50 [0.019"]
 $.x$ ±0.20 [0.008"]
 $.xx$ ±0.10 [0.004"]
 ANGLES ±1°

TITLE:
 Power Divider, 8 Way,
 2.35~2.55GHz, 300W,
 N & SMA-Female
 PART No.:
 TMPD8-02350255-300NS

 成都巨人微波
TITAN MICROWAVE INC.
- A Professional RF & Microwave Components Supplier -

www.titan-microwave.com

 DIMENSIONS IN MILLIMETERS(mm)
 SIZE: A4 SCALE: SHEET: 1/1 REV: A