REV	DESCRIPTION OF REVISION	Ву	DATE	APPROVED
Α	INITIAL RELEASE	C. Cai	2023/9/12	C. Chen

# TECHNICAL DATA

# ► Electrical Data

Pass Band FrequencyDC-1GHzPass Band Insertion Loss≤2.0dBPass Band VSWR≤1.5:1

Stop Band Rejection ≥60dB@1.3~6GHz

Impedance 50 Ohms

Power Handling ≤5W(design assurance)

### ► Mechanical Data


Dimensions 40.4×12×10mm

Connectors SMA-Female(stainless steel)

Surface Finish Silver Plated

#### ► Environmental Data

Temperature Range -40℃~+85℃(design assurance)



# Notes: 1. ALL SPECI

- 1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- 2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

V	DRAWN: L. M	23				
	ENGINEER: J. Zhu 12/09/23					
	APPROVED: C. Chen 12/09/23					
	TOLERANCE UNLESS OTHERWISE SPECIFIED					
	x	±0.50	[0.019"]			
	.x	±0.20	[0.008"]			
	.xx	±0.10	[0.004"]			
	ANGLES	±1°				

TITLE:

Low Pass Filter, DC-1GHz, Stop Band Rejection 60dB, 5W, SMA-Female

PART No.:

TLF-1000-S60



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE:

SCALE:

SHEET: F

REV: