

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/12/21	C. Chen

TECHNICAL DATA

► Electrical Data

Frequency Range	500~26500MHz
Nominal Coupling	20±2.5dB
Insertion Loss	2.5dB max
Main Line VSWR	1.24:1 typ, 1.7:1 max
Coupled Line VSWR	1.24:1 typ, 1.7:1 max
Directivity	10dB min
Frequency Sensitivity	±1.0dB typ, ±1.5dB max
Impedance	50 Ohms
Average Power	30W

► Mechanical Data

Input/Output Connectors	SMA-Female
Body Material	Aluminum
Surface Finish	Black Paint
Dimensions	154.5×15×11mm

► Environmental Data

Operating Temperature -45°C~+85°C



Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 21/12/22	TITLE: Directional Coupler 0.5-26.5GHz, Coupling 20dB, 30W SMA-Female	PART No.: TMDC-00502650-20S30	DIMENSIONS IN MILLIMETERS(mm)
ENGINEER: J. Zhu 21/12/22			
APPROVED: C. Chen 21/12/22			
TOLERANCE UNLESS OTHERWISE SPECIFIED			
x ±0.50 [0.019"]			
.x ±0.20 [0.008"]			
.xx ±0.10 [0.004"]			
ANGLES ±1°			
SIZE: A4	SCALE:	SHEET: 1/1	REV: A

TITAN MICROWAVE INC.
- A Professional RF & Microwave Components Supplier -

www.titan-microwave.com