

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/4/18	C. Chen

TECHNICAL DATA

► Electrical Data


Pass Band Frequency	DC-2000MHz
Pass Band Insertion Loss	≤1.0dB
Pass Band VSWR	≤1.3:1
Stop Band Rejection	≥80dB@2300~3500MHz
Impedance	50 Ohms
Power Handling	200W(design assurance)

► Mechanical Data

Dimensions	144×60×20mm
Connectors	N-Female
Surface Finish	Natural Color Conductive Oxidation
Body	Aluminum 6061
Weight	440g

► Environmental Data

Temperature Range	-40°C~+70°C(design assurance)
-------------------	-------------------------------



Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 18/04/23
ENGINEER: J. Zhu 18/04/23
APPROVED: C. Chen 18/04/23
TOLERANCE UNLESS OTHERWISE SPECIFIED
x ±0.50 [0.019"]
.x ±0.20 [0.008"]
.xx ±0.10 [0.004"]
ANGLES ±1°

TITLE:
Low Pass Filter
DC-2000MHz, Stop Band
Rejection 80dB, 200W, N-
Female

PART No.:
TLF-2000-80N

TITAN MICROWAVE INC.
A Professional RF & Microwave Components Supplier

www.titan-microwave.com

 DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE: 1:1	SHEET: 1/1	REV: A
----------	------------	------------	--------