

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/9/16	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	9.3~9.5GHz
Insertion Loss	0.3dB max
VSWR	1.2:1 max
Isolation	23dB min
Forward Power	30W
Reverse Power	10W
Direction	Clockwise
Impedance	50 Ohms

► Mechanical Data

Dimensions	12×20×13mm
Connector	SMA-Female
Material	Aluminum
Surface Finish	Nickel Plated
Weight	15g


► Environmental Data

Operating Temperature	-10℃~+60℃
Storage Temperature	-50℃~+90℃



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 16/09/23			TITLE: Coaxial Isolator 9.3-9.5GHz, 30W, SMA-Female	 成都巨人微波 TITAN MICROWAVE INC. - A Professional RF & Microwave Components Supplier -								
ENGINEER: J. Zhu 16/09/23												
APPROVED: C. Chen 16/09/23					PART No.: TMCI-09300950-30		DIMENSIONS IN MILLIMETERS(mm)		SIZE: A4	SCALE:	SHEET: 1/1	REV: A
TOLERANCE UNLESS OTHERWISE SPECIFIED												
x	±0.50	[0.019"]										
.x	±0.20	[0.008"]										
.xx	±0.10	[0.004"]										
ANGLES	±1°											