

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/9/16	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	6~10GHz
Insertion Loss	0.5dB max
VSWR	1.35:1 max
Isolation	17dB min
Forward Power	30W
Reverse Power	10W
Direction	Clockwise
Impedance	50 Ohms

► Mechanical Data

Dimensions	13×19×12.7mm
Connector	SMA-Female
Material	Aluminum
Surface Finish	Nickel Plated
Weight	20g


► Environmental Data

Operating Temperature	-10℃~+60℃
Storage Temperature	-50℃~+90℃



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 16/09/23			TITLE: Coaxial Isolator 6-10GHz, 30W, SMA-Female	 成都巨人微波 TITAN MICROWAVE INC. - A Professional RF & Microwave Components Supplier -	www.titan-microwave.com					
ENGINEER: J. Zhu 16/09/23					 DIMENSIONS IN MILLIMETERS(mm)	SIZE:		SCALE:	SHEET:	REV:
APPROVED: C. Chen 16/09/23						A4			1/1	A
TOLERANCE UNLESS OTHERWISE SPECIFIED						PART No.:		TMCI-06001000-30		
x	±0.50	[0.019"]								
.x	±0.20	[0.008"]								
.xx	±0.10	[0.004"]								
ANGLES	±1°									