

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2021/3/13	C. Chen

TECHNICAL DATA

► Electrical Data

Frequency Range	1.8~2.4GHz
Insertion Loss	0.5dB max
Isolation	18dB min
VSWR	1.3:1 max
Impedance	50 Ohms
Forward Power(CW)	150W
Reverse power	100W
Rotation	Clockwise


► Mechanical Data

Input/Output Connectors	N-Female
Material	Aluminum
Surface Treatment	Nicke Plated
Dimensions	25.4×28.5×15mm
Weight	100g

► Environmental Data

Operating Temperature	-30℃~+75℃
Storage Temperature	-50℃~+90℃

All the materials are RoHS Compliance



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 13/03/21		
ENGINEER: J. Zhu 13/03/21		
APPROVED: C. Chen 13/03/21		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

TITLE:

Coaxial Isolator,
1.8~2.4GHz, 150W,
N-Female

PART No.:

TMCI-01800240-150N



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------