

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/9/16	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	1.5~1.7GHz
Insertion Loss	0.4dB max
VSWR	1.25:1 max
Isolation	20dB min
Forward Power	100W
Reverse Power	20W
Direction	Clockwise
Impedance	50 Ohms

► Mechanical Data

Dimensions	19×19×8.6mm
Connector Type	Stripline
Material	Aluminum
Surface Finish	Nickel Plated
Weight	18g

► Environmental Data

Operating Temperature	-30℃~+75℃
Storage Temperature	-50℃~+90℃



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 16/09/23	TITLE: Drop-in Isolator 1.5-1.7GHz, Clockwise 100W	 www.titan-microwave.com		
ENGINEER: J. Zhu 16/09/23				
APPROVED: C. Chen 16/09/23		 DIMENSIONS IN MILLIMETERS(mm)		
TOLERANCE UNLESS OTHERWISE SPECIFIED				
x ±0.50 [0.019"]	PART No.: TMDI-100-01500170	SIZE: A4	SCALE:	SHEET: 1/1
.x ±0.20 [0.008"]				REV: A
.xx ±0.10 [0.004"]				
ANGLES ±1°				