

SPECIFICATIONS

Frequency Range:	DC~18GHz
Input Avg Power:	250W@25°C
Impedance:	50 Ohms
Attenuation:	10-60dB
VSWR:	1.45 max.
Connector:	N-Male to N-Female
Operating Temp.:	-55°C~+125°C
Connector Body:	Gold plated brass / Stainless steel
Female Center Contact:	Gold plated beryllium copper
Male Center Contact:	Gold plated brass
Heat Sink:	Black anodized aluminum
Dimensions:	254×110×120 mm
Weight	3.6kg
RoHS Status:	RoHS Compliant


Maximum Deviation over Frequency

Nominal ATTN(dB)	Frequency Range(GHz)			
	DC~4	DC~8	DC~12.4	DC~18
10	±0.7	±1.5	±2.5	±3.0
20	±0.7	±1.5	±2.5	±3.0
30	±0.8	±0.9	±1.0	±1.5
40	±0.9	±0.9	±1.1	±1.3
50~60	±0.9	±0.9	±1.1	±1.4
VSWR(Max.)	1.2	1.25	1.35	1.45

Ordering Information

TMFA18	X	N	250	-	XX
XX: Attenuation dB value					
Average Power(W)					
RF Connector (N: N-Male to N-Female)					
X: Maximum Frequency(GHz) 03: DC~3 GHz 12: DC~12.4 GHz 18: DC~18 GHz					
Titan Microwave Fixed Attenuator					

Power/Temp Rating Curve



Dimensions[mm]

