

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/9/16	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	225~270MHz
Insertion Loss	0.6dB max
VSWR	1.25:1 max
Isolation	19dB min
Forward Power	300W
Reverse Power	150W
Direction	Clockwise
Impedance	50 Ohms

► Mechanical Data

Dimensions	50.8×50.8×14.8mm
Connector Type	Stripline
Material	Aluminum
Surface Finish	Nickel Plated
Weight	220g

► Environmental Data

Operating Temperature	-30℃~+70℃
Storage Temperature	-50℃~+90℃



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 16/09/23			TITLE: Drop-in Isolator 225~270MHZ, Clockwise 300W	 成都巨人微波 TITAN MICROWAVE INC. - A Professional RF & Microwave Components Supplier -			
ENGINEER: J. Zhu 16/09/23				www.titan-microwave.com			
APPROVED: C. Chen 16/09/23							
TOLERANCE UNLESS OTHERWISE SPECIFIED				PART No.: TMDI-00220027-300	 DIMENSIONS IN MILLIMETERS(mm)		
x	±0.50	[0.019"]	SIZE: A4		SCALE:	SHEET: 1/1	REV: A
.x	±0.20	[0.008"]					
.xx	±0.10	[0.004"]					
ANGLES ±1°							