

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2025/4/30	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	500~3000MHz
Coupling	40±1.0dB
Coupling Flatness	±0.5dB max
Insertion Loss	0.35dB max
Primary Line VSWR	1.25:1 max
Directivity	18dB min
Impedance	50 Ohms
Primary Line Power	200W(CW)

► Mechanical Data

Primary Line Connectors	N-Female
Coupled Connectors	SMA-Female
Housing Material	Aluminum
Surface Finish	Conductive Oxidation
Dimensions	63.5×38.1×22.86mm

► Environmental Data

Operating Temperature	-55℃~+85℃
-----------------------	-----------



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 30/04/25
ENGINEER: J. Zhu 30/04/25
APPROVED: C. Chen 30/04/25
TOLERANCE UNLESS OTHERWISE SPECIFIED
x ±0.50 [0.019"]
.x ±0.20 [0.008"]
.xx ±0.10 [0.004"]
ANGLES ±1°

TITLE:

Dual Directional Coupler,
500~3000MHz, 40dB, 200W,
N-Female & SMA-Female

PART No.:

TDDC-00500300-40NS200



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE:	SCALE:	SHEET:	REV:
A4		1/1	A