

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2025/4/30	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	4KHz~400MHz
Coupling	50±1.0dB
Coupling Flatness	±0.6dB max
Insertion Loss	0.4dB max
Primary Line VSWR	1.3:1 max
Directivity	18dB min
Impedance	50 Ohms
Primary Line Power	300W(CW)

► Mechanical Data

Primary Line Connectors	N-Female
Coupled Connectors	SMA-Female
Housing Material	Aluminum
Surface Finish	Conductive Oxidation
Dimensions	152.4×55.9×55.9mm

► Environmental Data

Operating Temperature	-55℃~+85℃
-----------------------	-----------



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 30/04/25			TITLE: Dual Directional Coupler, 4KHz~400MHz, 50dB, 300W, N-Female & SMA-Female		成都巨人微波 TITAN MICROWAVE INC. - A Professional RF & Microwave Components Supplier -			
ENGINEER: J. Zhu 30/04/25					www.titan-microwave.com			
APPROVED: C. Chen 30/04/25								
TOLERANCE UNLESS OTHERWISE SPECIFIED			PART No.: TDDC-4K400M-50NS300		DIMENSIONS IN MILLIMETERS(mm)			
x ±0.50 [0.019"]					SIZE: A4 SCALE: SHEET: 1/1 REV: A			
.x ±0.20 [0.008"]								
.xx ±0.10 [0.004"]								
ANGLES ±1°								