

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2025/3/24	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	10~512MHz
Nominal Coupling	30±1dB
Coupling Flatness	±1.0dB max
Insertion Loss	1.0dB max
Primary Line VSWR	1.3:1 max
Directivity	18dB
Impedance	50 Ohms
Power Rating	300W(CW)

► Mechanical Data

Input/Output Connectors	N-Female
Coupled Connector	SMA-Female
Body Material	Aluminum
Surface Finish	Conductive Oxide
Dimensions	130×55.9×55.9mm

► Environmental Data

Operating Temperature	-55℃~+85℃
-----------------------	-----------



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 24/03/25
ENGINEER: J. Zhu 24/03/25
APPROVED: C. Chen 24/03/25
TOLERANCE UNLESS OTHERWISE SPECIFIED
x ±0.50 [0.019"]
.x ±0.20 [0.008"]
.xx ±0.10 [0.004"]
ANGLES ±1°

TITLE:

Single Directional Coupler,
10~512MHz
Coupling 30dB, 300W
N-Female & SMA-Female

PART No.:

TMDC-10M512M-30NS300



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE:	SCALE:	SHEET:	REV:
A4		1/1	A