

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/12/21	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	2000~2300MHz
Insertion Loss(average)	0.3dB max
VSWR	1.2:1 max
Isolation	20dB min
Amplitude Balance	±0.2dB max
Phase Balance	±3°
Impedance	50 Ohms
Power Rating	500W(CW)

► Mechanical Data

Input/Output Connectors	DIN 7/16(L29)-Female
Dimensions	89×50×35mm
Surface Finish	Natural Color Conductive Oxidation

► Environmental Data

Operating Temperature	-55℃~+70℃
-----------------------	-----------



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 21/12/22			TITLE: 3dB 90° Hybrid Coupler, 2000~2300MHz, 500W, DIN 7/16(L29)-Female		 成都巨人微波 TITAN MICROWAVE INC. <i>- A Professional RF & Microwave Components Supplier -</i> www.titan-microwave.com				
ENGINEER: J. Zhu 21/12/22									
APPROVED: C. Chen 21/12/22			PART No.: TMHC90-02000230-500D		 DIMENSIONS IN MILLIMETERS(mm) SIZE: A4 SCALE: SHEET: 1/1 REV: A				
TOLERANCE UNLESS OTHERWISE SPECIFIED									
x	±0.50	[0.019"]							
.x	±0.20	[0.008"]							
.xx	±0.10	[0.004"]							
ANGLES	±1°								

x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	