

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/12/21	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	6000~12000MHz
Insertion Loss(average)	0.8dB max
VSWR	1.6:1 max
Isolation	16dB min
Amplitude Balance	±0.5dB max
Phase Balance	±5° max
Impedance	50 Ohms
Power Rating	100W(CW)

► Mechanical Data

Connectors	SMA-Female
Dimensions	35.7×25×11mm
Surface Finish	Natural Color Conductive Oxidation

► Environmental Data

Operating Temperature	-55℃~+85℃
-----------------------	-----------



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 21/12/22			TITLE: 3dB 90° Hybrid Coupler, 6000~12000MHZ, 100W, SMA-Female	 成都巨人微波 TITAN MICROWAVE INC. <i>- A Professional RF & Microwave Components Supplier -</i>			
ENGINEER: J. Zhu 21/12/22							
APPROVED: C. Chen 21/12/22							
TOLERANCE UNLESS OTHERWISE SPECIFIED				 DIMENSIONS IN MILLIMETERS(mm)			
x	±0.50	[0.019"]					
.x	±0.20	[0.008"]					
.xx	±0.10	[0.004"]					
ANGLES ±1°			PART No.:	SIZE:	SCALE:	SHEET:	REV:
			TMHC90-06001200-100S	A4		1/1	A