

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/12/21	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	1745~2125MHz
Insertion Loss(average)	0.3dB max
VSWR	1.3:1 max
Isolation	20dB min
Amplitude Balance	±0.5dB max
Phase Balance	±5° max
Impedance	50 Ohms
Power Rating	800W(CW)

► Mechanical Data

Connectors	DIN 7/16(L29)-Female & N-Female
Dimensions	111×48×32mm
Surface Finish	Natural Color Conductive Oxidation

► Environmental Data

Operating Temperature	-55℃~+85℃
-----------------------	-----------



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 21/12/22
ENGINEER: J. Zhu 21/12/22
APPROVED: C. Chen 21/12/22
TOLERANCE UNLESS OTHERWISE SPECIFIED
x ±0.50 [0.019"]
.x ±0.20 [0.008"]
.xx ±0.10 [0.004"]
ANGLES ±1°

TITLE:

3dB 90° Hybrid Coupler,
1745~2125MHz, 800W,
DIN 7/16(L29)-Female &
N-Female

PART No.:

TMHC90-01740212-800DN



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------