

TECHNICAL DATA

► Electrical Data


Frequency Range	1500~1700MHz
Insertion Loss(average)	0.4dB max
VSWR	1.35:1 max
Isolation	18dB min
Amplitude Balance	±0.3dB max
Phase Balance	±6° max
Impedance	50 Ohms
Power Rating	300W

► Mechanical Data

Input/Output Connectors	N-Female
Dimensions	65×70×22mm
Surface Finish	Natural Color Conductive Oxidation

► Environmental Data

Operating Temperature	-55℃~+85℃
-----------------------	-----------



REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/12/21	C. Chen

Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 21/12/22		
ENGINEER: J. Zhu 21/12/22		
APPROVED: C. Chen 21/12/22		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

TITLE:

3dB 180° Hybrid Coupler,
1500~1700MHz, 300W,
N-Female

PART No.:

TMHC180-01500170-300N



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------