

TECHNICAL DATA

► Electrical Data

Frequency Range	800~1000MHz
Insertion Loss	0.1dB max
VSWR	1.2:1 max
Coupling	20±1.0dB
Directivity	25dB min
Power Handling	25W(CW)


► Mechanical Data

Dimensions	6.35×5.08×2.0mm
Connector Type	SMD
Surface Finish	Immersion Gold


► Environmental Data

Operating Temperature	-55℃~+105℃
-----------------------	------------

Pin Configuration




Top View



Side View



Bottom View



Pin 1	Pin 2	Pin 3	Pin 4
Input	Transmission	Isolate	Coupling
Transmission	Input	Coupling	Isolate

Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 16/04/22
ENGINEER: J. Zhu 16/04/22
APPROVED: C. Chen 16/04/22
TOLERANCE UNLESS OTHERWISE SPECIFIED
x ±0.50 [0.019"]
.x ±0.20 [0.008"]
.xx ±0.10 [0.004"]
ANGLES ±1°

TITLE:

SMD Directional Coupler,
800~1000MHz, 20dB,
25W

PART No.:

TMDC0900P20



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE:
A4

SCALE:

SHEET:
1/1

REV:
A