

TECHNICAL DATA

► Electrical Data

Frequency Range	680~2700MHz
Insertion Loss	0.2dB max
VSWR	1.15:1 max
Coupling	20±1.2dB
Directivity	23dB min
Power Handling	150W(CW)


► Mechanical Data

Dimensions	25.4×12.7×1.3mm
Connector Type	SMD
Surface Finish	Immersion Gold

► Environmental Data

Operating Temperature	-55℃~+105℃
-----------------------	------------




Pin Configuration



Top View

Side View

Bottom View



Pin 1	Pin 2	Pin 3	Pin 4
Input	Direct	Isolatd	Coupled
Direct	Input	Coupled	Isolatd
Isolatd	Coupled	Input	Direct
Coupled	Isolatd	Direct	Input

Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 16/04/22
ENGINEER: J. Zhu 16/04/22
APPROVED: C. Chen 16/04/22
TOLERANCE UNLESS OTHERWISE SPECIFIED
x ±0.50 [0.019"]
.x ±0.20 [0.008"]
.xx ±0.10 [0.004"]
ANGLES ±1°

TITLE:

SMD Directional Coupler,
680~2700MHz, 20dB,
150W

PART No.:

TMDC1700B20



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE:
A4

SCALE:

SHEET:
1/1

REV:
A