

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/4/12	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	20~1000MHz
Coupling	50±1.5dB
Coupling Flatness	±1.0dB max
Insertion Loss	0.35dB max
VSWR(Primary Line)	1.25:1 max
Directivity	18dB min
Main Line Power	300W(CW) max

► Mechanical Data

Connector Type	SMD
Surface Finish	Immersion Gold
Dimensions	38.1×25.4×3.7mm

► Environmental Data

Operating Temperature	-55℃~+85℃
-----------------------	-----------



IN	OUT	Forward Coupled	Reflected Coupled
J1	J2	J3	J4
J2	J1	J4	J3

Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 12/04/23		
ENGINEER: J. Zhu 12/04/23		
APPROVED: C. Chen 12/04/23		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

TITLE:

SMD Directional Coupler,
20~1000MHz, 300W,
50±1.5dB

PART No.:

TM0126-50-300



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------