

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/4/12	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	2700~6200MHz
Coupling	9±0.5dB
Coupling Flatness	±1.0dB max
Insertion Loss	1.0dB max(including theoretical loss 0.58dB)
VSWR	1.3:1 max
Directivity	15dB min
Primary Line Power	100W(CW)

► Mechanical Data

Connector Type	SMD
Surface Finish	Immersion Gold
Dimensions	14.22×5.08×1.7mm max

► Environmental Data

Operating Temperature	-55℃~+85℃
-----------------------	-----------



IN	OUT	Forward Coupled	Reflected Coupled
J1	J4	J2	J3
J4	J1	J3	J2

Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 12/04/23		
ENGINEER: J. Zhu 12/04/23		
APPROVED: C. Chen 12/04/23		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

TITLE:

SMD Directional Coupler,
2700~6200MHz, 100W, 9dB

PART No.:

TM013208-9



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------