

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/4/16	C. Chen

TECHNICAL DATA

► Electrical Data

Frequency Range	DC~6GHz
VSWR	1.15:1 max
Impedance	50 Ohms
Input Power	2 Watts Avg.@25℃

► Mechanical Data


Durability	500 Cycles min.
Connector Type	NEX10-Male

► Material & Finishing

Body	Brass, Ternary Alloy Plating
Center Conductor	Brass, Gold Plating
Other Metal Part	Ternary Alloy Plating


► Environmental Data

Operating Temperature	-40℃~+125℃
-----------------------	------------



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 16/04/22	TITLE: Coaxial Termination DC~6GHz, 2W NEX10-Male	 成都巨人微波 TITAN MICROWAVE INC. - A Professional RF & Microwave Components Supplier -		
ENGINEER: J. Zhu 16/04/22				
APPROVED: C. Chen 16/04/22		www.titan-microwave.com		
TOLERANCE UNLESS OTHERWISE SPECIFIED		 DIMENSIONS IN MILLIMETERS(mm)		
x ±0.50 [0.019"]	PART No.: TMT62XM	SIZE: A4	SCALE:	SHEET: 1/1
.x ±0.20 [0.008"]				REV: A
.xx ±0.10 [0.004"]				
ANGLES ±1°				