

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/3/26	C. Chen

TECHNICAL DATA

► Electrical Characteristic


Frequency Range	DC~40GHz
Impedance	50 Ohms
VSWR	1.15:1 max
Mating Cycles	500 min

► Material & Finishing

Center Conductor	Beryllium Copper, Gold Plated
Outer Conductor	Passivated Stainless Steel
Insulators	PEI


► Environmental

Temperature Range	-40°C~+125°C
-------------------	--------------



Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 26/03/22	TITLE:	 成都巨人微波 TITAN MICROWAVE INC. <i>- A Professional RF & Microwave Components Supplier -</i>		
ENGINEER: J. Zhu 26/03/22	PART No.:			
APPROVED: C. Chen 26/03/22	TMCAKKFA	 DIMENSIONS IN MILLIMETERS(mm)		
TOLERANCE UNLESS OTHERWISE SPECIFIED	SIZE: A4	SCALE: 1/1	SHEET: 1/1	REV: A
x ± 0.50 [0.019"] .x ± 0.20 [0.008"] .xx ± 0.10 [0.004"] ANGLES $\pm 1^\circ$				