

TECHNICAL DATA

► Electrical Data




Frequency Range	9.84~15GHz
VSWR	1.2:1 max
Average Power	250W(CW, max)

► Mechanical Data

Waveguide Type	WR-75
Flange	FBP120
Cooling	Natural Cooling
Material	Aluminum
Surface Treatment	Conductive Oxidation
Surface Finish	T.Matte Back.III.Y

► Environmental Data

Operating Temperature	-40℃~+70℃
-----------------------	-----------



REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2026/2/4	C. Chen

Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 04/02/26
ENGINEER: J. Zhu 04/02/26
APPROVED: C. Chen 04/02/26
TOLERANCE UNLESS OTHERWISE SPECIFIED
x ±0.50 [0.019"]
.x ±0.20 [0.008"]
.xx ±0.10 [0.004"]
ANGLES ±1°

TITLE:

Waveguide Medium Power
Termination,
9.84~15GHz, 250W, WR-75

PART No.:

TWTM75P250W



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------